

Recessed Track Gantry Roller

By:



 Safety! Dual safety bars and a strobe warning light.

 Low Maintenance. Easily accessible grease points.

 Heavy Duty Steel Roll with 1" wall.

 120+ Feet Per Minute working speed

 Rail is recessed under tables.

 8 Klaisler Bogie Wheels.

Visit us on the Web at:
WWW.KLAISLER.COM



A Klaisler gantry roller system is designed to provide consistent operation and long life. Our updated 15 hp motor package and 4 wheel drive that is recessed under the table, provides a 120 feet per minute working speed. The Gantry weighs in at 8,500 pounds, and with its 24" diameter 1" wall roll, will pre set your plates. A solid state VFD control system with the latest Klaisler Easy ID Software Package, provides easy to ready "Plain English" information from the control. No more light flashes or codes to memorize

We offer a wide variety of tables tops and sizes to fit your requirements. From the solid Durawood tops to our latest WEG-IT solid steel tops, you can choose from 12 standard 6' and 8' wide models or we can manufacture special tables and equipment to meet your specific requirements.

Don't take chances with equipment that your business depends on, invest in a Klaisler gantry roller system and experience the difference.

TOUGH

Heavy duty structural steel and quality components assure longevity despite tough working conditions

SAFE

Failsafe brakes and safety bars front and rear protect your employees and ensure safety. Our Alert Strobe flashes just prior to and while the machine is in operation.

SERVICE

50 years of manufacturing equipment for the truss building industry.
Service and support when you need it, where you need it.



Our latest engineering development, the WEG-IT system provides you not only with positive puck placement but a variety of jiggging options including the "Peak Puck". Contact our office for more information on your table and jiggging choices.



Control Cabinet with drive window.



Operators Pendant

SPECIFICATIONS

Rail Recessed under table

Heavy duty steel roll -24" diameter with 1" wall thickness

3" or 4" diameter shafts available, 4 baffles per roll with Spherical roller bearings

2 Sumitomo braking gear motors

7.5 horsepower (total of 15HP)

230 or 460 volt 3 phase power

failsafe brakes

Soft start inverter package (120' per minute plus!)

Klaisler easy ID software package

Easily accessible grease fittings

8 - bogie wheels

4 - 10" drive wheels

Safety bars front and rear with proximity sensors

Flashing motion indicator light

Specification subject to change without notice.